

Technics SA-GX200, Sherwood RX-4010R, Sony STR-AV220, Kenwood KR A-2080, Kenwood KR-A5050, Audion A-900 pojačalo i T900 tjuner (by Marentz)

Cena: 60,00 EUR

www.oglas.rs

Kategorija: Kućni audio sistemi (Audio, TV, foto)

Lokacija: Novi Sad grad (Srbija, Novi Sad)

Kategorije: Risiveri

Garancija: Nema

Stanje: Korišteno

Šifra oglasa: 03-3745380

Datum postavljanja oglasa: 05.01.2026

Kontakt: Komazec Zeljko

Telefon: 0642393714



Dodatne informacije:

Tekst oglasa:

1. Technics SA-GX200 (60 eur) 2x60w/4ohm, i 2x50w/8ohm
Connection options for: Phono, CD, Tape, VCR 1 and VCR 2
Connection option for 2 pairs of speakers Bass, treble and balance
variably adjustable loudness Odpowiedź częstotliwościowa: od 7
Hz do 40 kHz Całkowite zniekształcenia harmoniczne: 0,03%
Czułość wejścia: 3mV (MM), 200mV (linia) Stosunek sygnału do
szumu: 80 dB (MM), 90dB (linia) Wyjście: 200mV (linia)
Impedancja obciążenia głośnika: 4Ω (minimum) Dimenzije: 430 x
124 x 300 mm Tezina: oko 6,5 kg 2. Sherwood RX-4010R (65
eur) Američki inžinjering u saradnji sa Japancima a proizveden u
Južnoj Koreji sa PRE OUT i PRE IN ulazima, može raditi kao
pretpojačalo. Podržava zvučnike od 4 do 16 oma. Specifications
Tuning range: FM, MW Power output: 60 watts per channel into 8Ω
(stereo) Frequency response: 5Hz to 60kHz Total harmonic
distortion: 0.08% Damping factor: 70 Input sensitivity: 2.5mV
(MM), 150mV (line) Signal to noise ratio: 73dB (MM), 95dB (line)
Speaker load impedance: 4Ω (minimum) Dimensions: 440 x 125 x
280mm Weight: 7.2kg 3. Sony STR-AV220 (55 eur) Audio Video
Control Center (1990-91) Specifikacija: Power output: 40 W po
kanalu na 8Ω (stereo) Frequency response: 10Hz to 50kHz Total
harmonic distortion: 0.8% Input sensitivity: 2.5mV (MM), 150mV
(line) Signal to noise ratio: 74dB (MM), 95dB (line) Output: 150mV
(line) Speaker load impedance: 8Ω to 16Ω Dimenzije: 430 x 110 x
295 mm Tezina: 5,2 kg 4. Kenwood KR A-2080 (50 eur) stereo
risiver Specifications (Phono, CD, Tape, Video) Tuning range: FM,
MW Power output: 50 watts per channel into 4Ω (stereo)
Frequency response: 20Hz to 20kHz Total harmonic distortion:

0.03% Input sensitivity: 2.5mV (MM), 200mV (line) Signal to noise ratio: 52dB (MM), 53dB (line) Speaker load impedance: 4Ω (minimum) Dimenzije: 440 x 127 x 380 mm tezina: 6.7kg 5. Kenwood KR-A5050 (65 eur) stereo risiver Power consumption: 180 W Dimensions (WxHxD): 440 x 133 x 350 mm Tezina oko: 10.2 kg Original price approx. : 599 DM Number of inputs: 1x Phono MM (Cinch) 1x CD/AUX In (Cinch) 2x Tape In (Cinch) 2x Video In (Cinch) FM antenna AM antenna Number of outputs: 2x Tape Out (Cinch) Headphones (6,3mm jack) 2 pairs of loudspeakers Technical Data Amplifier Continuous power (at distortion) 8 Ohm: 2x 105 W (IHF'66) 4 Ohm: Dynamic power 8 Ohm: 4 Ohm: Total harmonic distortion: 0.03% (1 kHz with 50 W at 8 ohms). Attenuation factor: Frequency response (IHF'66): 20 to 20,000 Hz. Signal-to-noise ratio (IHF'66): Phono MM: 73 dB Line: 100 dB Stereo channel separation: Tone control: Bass: yes (±10 dB at 100 Hz) Treble: yes (±10 dB at 10 kHz) Loudness: yes (at -30dB volume approx. +8 dB at 100 Hz) High Filter: Low Filter (Subsonic): Mute: yes Direct/Line-Straight: Tuner Reception: FM, AM Frequencies: FM: 87.5 - 108 MHz AM (at 9kHz steps): 531 - 1602 kHz AM (at 10kHz steps): 530 - 1610 kHz Frequency response: 30 - 15,000 Hz Input sensitivity: FM: 1.3 μ F AM: 40 μ F Distortion factor: FM: 0.4% (mono), 0.5% (stereo) (each at 65 dBf input signal) Distortion factor: AM: 0.5% (mono), 0.4% (stereo) Signal-to-noise ratio: FM: 78 dB (mono), 73 dB (stereo) (each at 65 dBf input signal). AM: 50 db (30% mod. 1 mV input signal). Channel separation: Selectivity: Co-wave selection: Spurious wave selection: IF attenuation: IF attenuation: Output level: RDS: yes Station memory: yes/2 RDS 6. Audion A-900 pojačalo i T900 tjuner (70 eur) (by Marentz)

www.oglas.rs

Free Press d.o.o Šafarikova 15, 21000 Novi Sad, +381 21 48 04 555